

nexus[®]
ELECTRONICS



Nexus Electronics offers cutting edge Flat Panel Display Technology at a very affordable price.

At Nexus Electronics we have never produced an Analog Television. We were Born Digital. Our Progressive Scan LCD and Plasma High Definition Displays offer stunning picture quality and versatile connectivity for a wide range of home entertainment applications.

Whether you are watching a movie, playing video games, or surfing the internet, Nexus High Definition Televisions are the right choice.

Plasma Televisions





		NEXUS NX422 42"	NEXUS NX503P 50"	NEXUS NX603P 60"
Display Features	Display Type	Plasma Display Panel (PDP)	Plasma Display Panel (PDP)	Plasma Display Panel (PDP)
	Screen Size	42" Wide Screen	50" Wide Screen	60" Wide Screen
	Resolution	1024 x 768	1920 x 1080	1920 x 1080
	HD Ready	1080i, 720p, 480i/p	1080p/i, 720p, 480i/p	1080p/i, 720p, 480i/p
	Chipset Solution	MSTAR	M-Tek	M-Tek
	Contrast Ratio	10,000:1	30,000:1	30,000:1
	Brightness	1200 cd/m2	1000 cd/m2	1000 cd/m2
	Pixel Pitch	900 (H) x 676 (V)	900 (H) x 676 (V)	1.02mm (H) x 1.02mm (V)
	Progressive Scan	Yes	Yes	Yes
	Comb Filter	3D Digital Comb Filter	3D Digital Comb Filter	3D Digital Comb Filter
	Noise Reduction	Yes	Yes	Yes
	Aspect Ratio	16:9	16:9	16:9
Audio	Speakers	Embedded 10W x 2	Embedded 10W x 2	Embedded 10W x 2
	Audio Type	SRS (option) / BTSC/MTS/AC-3	Stereo, SAP/AC3 Dolby	Stereo, SAP/AC3 Dolby
Reception	TV System	NTSC/ATSC	NTSC/ATSC	NTSC/ATSC
	Channel Coverage	VHF 2-13, UHF 14-69, CATV (1-125)	VHF 2-13, UHF 14-69, CATV (1-125)	VHF 2-13, UHF 14-69, CATV (1-125)
	Tuner	ATSC/ NTSC/Clear QAM	ATSC/ NTSC/Clear QAM	ATSC/ NTSC/Clear QAM
Terminals	RF: TV/Coaxial	1	1 Digital and Analog	1 Digital and Analog
	RCA Composite A/V Input	2	2	2
	S-Video: 4-pin DIN	1	2	2
	HDMI Input	2 (DVI Compatible)	3 (Ver. 1.3)	3 (Ver. 1.3)
	Component Video	YPbPr/YCbCr x 2	YPbPr/YCbCr x 2	YPbPr/YCbCr x 2
	Component Video	L/R RCA x 2	L/R RCA x 2	L/R RCA x 2
	RCA A/V Out	1	1	1
	Earphone Jack	1	1	1
	Speakers Out	L & R	L & R	L & R
	VGA	No	Yes	Yes
Other Features	Wall Mount Support	Yes (Universal)	Yes (Universal)	Yes (Universal)
	Power Supply	AC 100-240V 60/50Hz	AC 120, 60Hz	AC 120, 60Hz
	Power Consumption	400W and 1W Stand By	400W and 1W Stand By	550W and 1W Stand By
	Safety and Regulation	UL, CUL approved	UL, CUL approved	UL, CUL approved
	Dimensions (W x H x D) Inches	w/Stand & Speakers: 41.25 x 32 x 12.5	w/Stand: 49 x 36 x 14.25	w/Stand: 58 x 41 x 15
	Weight (Pounds)	Net: 86 / Gross: 112	Net: 94 / Gross: 121	Net: 152 / Gross: 240
	Warranty	1 Year Warranty	2 Year Parts and Labor	2 Year Parts and Labor